SPECIALTY HAND TOOLS COMPLETE TOOL KITS FOR FAST, CONVENIENT REPAIRS

Visit us online at www.cpsproducts.com

UNIVERSAL R-410A SERVICE TOOL KITS

Our tool kits contain everything you need to service ductless mini-split and central A/C systems with 1/4" & 5/16" service ports including the following components;





Two Valve Service Manifold (Varies by kit. See chart below) R-410A/R-22/R404A gauges

- 1/4" SAE fittings
- Triple seal valve system



(1) Imperial and (1) Metric **Hex Key Set**

- Metric Set: 1.5, 2, 2.5, 3, 4, 5, 6.8 mm



2

Premium 3-Pack 5' Hoses (Varies by kit. See chart below)

- 1/4" SAE 45° fittings
- 800Psi working pressure
- 4000Psi burst pressure



Valve Core Tool

- 5/16" female fitting allows direct connection to mini-split service ports
- ⁵/₁₆" female x ¹/₄" SAE male



- Clutch driven feed screw
- Eccentrically mounted cone •
- Creates perfect, strong flares
- Ratchet drive in yoke ³/₁₆", ¹/₄", ¹/₁₆", ³/₈", ¹/₂" ¹/₈", ³/₄"



Brass Adapters and Caps

(10) ½"-20 UNF Caps, (2) Male: 1/4" SAE 55D; female; 1/2"-20 UNF SWVL, and (2) Male: 1/4" SAE female; 1/2"-20 UNF



CDS

Torque Wrench Sets;

TLB410A

- Metric Set: 12, 22, 24, 26, 27, 29 mm and ¹³/₁₆" jaw sizes • -or-
- Imperial Set: 5%", 11/16", 13/16", • ¹⁵/16", **1**¹/16", **1**⁵/16"



13" Large Square Tool Bag

- 24 separate compartments for ٠ quick, easy-access
- Molded handle for durability and comfort

Kit Contonto	04.	UNIVERSAL SERVICE TOO					
Kit Contents	Qty	TLB410A	TLB410SAE	TLB410KIT	TLB410AC	TLB410ACE	TLB410M
1 2 Valve Manifold	1	Pro-Set [®] Piston Pink Body ^{1/} 4" SAE 45° fittings "H" Gauge (MEHP5E)		Pro-Set® Premium Piston Series Manifold (#MT2HP)	BLACKMAX [®] Black & Chrome ¹ / ₄ " SAE 45° fittings "H5" Gauge (MBH5P5Z)	BLACKMAX [®] Black & Chrome ¼" SAE 45° fittings "H5" Gauge (MBH5P5EZ)	No Manifold
2 Hoses	1	Pro-Set [®] Premium (3) 5' red/blue/yellow ball valve hoses		ım llow s	Pro-Set [®] Premium (3) 5' Black & Chrome hoses	Pro-Set [®] Premium (3) 5' Black & Chrome ball valve hoses	No Hoses
3 Flaring Tool	1	FT8	00N	BFT850	FT800N		
4 Torque Wrench Set	1	Metric TLTWSM	SAE/Imperial TLTWSAE	Universal Handle with SAE/Imperial & Metric Heads			
5a Hex Wrench Set (Metric)	1	TLSWHM					
50 Hex Wrench Set (Imperial)	1	TLSWH					
b Valve Core Tool	1	TLVC410A					
7 Brass Adapters and Brass Caps	14	Includes; (10) AVC410 ½"-20 UNF SAE Brass Caps, (2) AD87 Brass Adapter Male: 1/4" SAE 55D; female; ½"-20 UNF SWVL w/ Valve Core Tool, and (2) AD87S Brass Adapter (Male: 1/4" SAE; female; ½"-20 UNF) w/Valve Core Tool					
8 Tool Bag	1	TLBAG1 TLBAG1 TLBAG1					

Call and speak to a specialist. | Toll Free: (800) 277-3808 | Customers outside the USA: (305) 687-4121



R410A SERVICE TOOL KIT

Tool kit includes:

- Pro-Set® Premium Piston Series • Manifold
- 5' Premium Pro-Set® Charging Hoses
- Imperial and Metric Hex Key Sets
- Valve Core Tool
- Brass Adapters and Caps •
- Large, 16" Rubber Bottom Tool • Organizer
- Imperial and Metric Torque Wrench • Set and Instructions
- BLACKMAX® Tube Cutter 1/8" to • 1-1/4"
- **BLACKMAX®** Tube Flaring Tool •
- BLACKMAX® Deburring Tool with • extra blade
- R410A Flare Size Gauge



Pro-Set[®] Premium Piston Series Manifold #MT2HP 2 valve anodized aluminum block

- body 1/4" SAE 45° fittings Triple Seal piston valves Sure grip rubber over metal valve
- •
- handles 3 1/8" (80 mm) Class 1.0 accuracy
- gauges
- Protective gauge boots
- Extra access port in center with Schrader valve and hanging hook



5' Premium Charging Hoses

#HP5BE-Blue, HP5RE-Red, HP5YE-Yellow

- 1/4" hoses with SAE fittings, 45° ball valve on one end
- 800PSI working pressure 4000PSI burst pressure Leak-proof 8-sided crimp

- Extra deep knurling ٠
- Adjustable valve core depressor
- Blow off grooves preventing spray back



Hex Key Sets (1) Imperial #TLSWH ⁵/64", ³/32", ⁷/64", ¹/8", ⁹/64", ⁵/32", ³/16", ⁷/32", ¹/4" (1) Metric #TLSWHM 1.5, 2, 2.5, 3, 4, 5, 6, 8mm



Valve Core Tool #TLVCS410A

Unique configuration of tool enables use of standard 1/4" SAE manifold/hose sets with R-410A systems incorporating 5/16" (1/2"-20UNF) service ports.

- Designed to remove and install valve core without losing system charge
- . Increases evacuation and charging speed by creating unrestricted access



Large, 16" Rubber Bottom Tool Organizer #TLBAG2

- Separate compartments for quick, easy-access
- Molded handle for durability and comfort
- Rubber bottom



BlackMAX[®] Tube Cutter 1/8" to

- 1-1/4" #BTC300
- Two quick-change, chromed, hardened cutting wheels
- Enclosed feed screw eliminates .
- clogging, jamming SetNCut™ spring-loaded cutting wheel for a perfect cut every time



BlackMAX® Tube Flaring Tool #BFT850

- Aluminum body is 50% lighter than steel designs
- Internal clutch indicates when formed flare is
- complete Eccentric cone forms precise 45° flared ends
- Creates perfect, strong flares For 3/16", 1/4" 5/16", 3/8", 1/2", 5/8", 3/4" O.D. soft copper, aluminum tube



Brass Adapters and Caps

- (10) 1/2"-20 UNF Caps #AVC410
- (2) Male: 1/4" SAE 55D; Female; 1/2"-20 UNF SWVL, #AD87S and
- (2) Male: 1/4" SAE Female; 1/2"-20 **ÜNF** #AD87



BlackMAX® Deburring Tool with extra blade inside handle •

- Quick-change blade
- Solid aluminum body •
- #BTLDB3



Torque Wrench Set with (1) Universal Handle #TLTWSAE and (6) Imperial and (6) Metric wrenches (part numbers below) and instructions

Heads				
	Metric	Imperial		
17mm	#TLXTWM17	5 %" #TLXTW58		
22mm	#TLXTWM22	¹¹ / ₁₆ "	#TLXTW1116	
24mm	#TLXTWM24	¹³ / ₁₆ "	#TLXTW1316	
26mm		¹⁵ / ₁₆ "	#TLXTW1516	
27mm	#TLXTWM27	1 ¹ /16"	#TLXTW1L116	
29mm	#TLXTWM29	1 ⁵ /16"	#TLXTW1L516	



R410A Flare Size Gauge

#FTXSG •

•

12

- 6.4 mm, 1/4"
- 9.5 mm, 3/8" • 12.7 mm, 1/2"
- 15.9 mm, 5/8"
- 19.1 mm, 3/4"

CPS® EXTRA DURABLE TOOL BAGS

Organize your tools with care with this extra strong, premium built series of tool bags from CPS.



TLBAG1 Square Tool Organizer

Specialty Hand Tools

ALUMINUM, RECHARGEABLE WORK LIGHT- WITH 53 LEDS, HANGING HOOK, CAR & WALL PLUG CHARGER

Simply the best work light you will ever own, the TLWL53A is precision machined from aircraft grade aluminum and anodized for long life. Fifty three proprietary high output LEDs are incorporated in the work light segment with a 1W Luxeon LED integrated in the top. A powerful 2500mAh Ni-Mh rechargeable battery keeps the lights burning for hours; 7-8 hr for Luxeon spot, 4-5 hr for 53 white LEDs. The professional quality and intense output of the TLWL53A outperforms many competitive units incorporating 70 or more standard LEDs. Ideal for air conditioning contractors municipalities, law enforcement, fire fighters,

TLBAG2 16" Rubber Bottom Tool Organizer

automotive technicians, and wherever else a high performance, professional, durable work light is needed.

- Rugged anodized aluminum body
- Super bright 1w Luxeon spot
- 53 Proprietary high lumen output LEDs
- Integrated 2500mah 3.5V rechargeable battery
- Strong magnetic base for attaching to metal surfaces
- Universal UL/CUL electronic wall and car chargers included
- Superior durability and shock resistance
- High quality reflector lens
 - Wall and car charger included
- One year warranty



TLBAG3 Tool Belt Tool Organizer











CPS® SOLENOID MAGNET

The TLMKC18 is designed to manually open solenoid valves by magnetically lifting the stem assembly and plunger. Simply slide the TLMKC18 over the valve's enclosing tube and the industrial grade magnets incorporated inside the rugged ABS plastic housing does the rest. It is an ideal tool for trouble shooting/servicing both direct connected or pilot operated 2-way solenoid, 3-way reclaim or 4-way reversing valves.


0.75"/18 mm opening fits all common • manufactured valves

CPS® COMPACT MAGNETIZER/DEMAGNETIZER

Use the TLMAG1 to magnetize tools in order to keep small screws and nuts in position, especially helpful when working in confined spaces, or demagnetize tools when working on or near electronic circuit boards. Simply insert a screwdriver or nut driver into the (+) opening, slowly draw it out and it's magnetized. Leave the magnetizer on the tool for extra strength. To demagnetize, slowly draw the tool through the smallest area of the (-) opening.

TLMKC18

- Instantly magnetize or demagnetize steel tools & parts
- Incorporates two C5 industrial strength magnets
- Impact resistant ABS molded plastic
- No batteries or electricity required •
- Compact design: 2" x 2" x 1"



CDS' TLMAGT TLMAG1

CPS® DUCT KNIVES

Used to fabricate fiberglass duct board. Stainless steel double edge resharpenable blade facilitates easy piercing for inside cuts. The double edge is also ideal for tapping into and trimming flex duct. Available with either ergonomic cushioned or a comfortable walnut wooden handle.

TLDWH 6" (152 mm) Duct Knife With Wood Handle

TLDKRH 6" (152 mm) Duct Knife With Rubber Handle

CDS

PRO-SET[®] ADJUSTABLE HANDLE WRENCH


- Patented light weight composite handle design
- Wide jaw opening with 45% more torque
- Precision machined for smooth operation
- Ergonomic, comfortable grip reduces fatigue
- Durable and environment-resistant
- Packed in clear clamshell
- with printed display card
- One year warranty



Size: 6" Jaw Capacity: 1⁵/₁₆" / 24 mm

TLWA08 Size: 8" Jaw Capacity: 1¹/₈" / 29 mm

TLWA10 Size: 10" Jaw Capacity: 1⁵/₁₆" / 33 mm



PRO-SET[®] SERVICE WRENCHES

- Metal construction
- Embossed fractions and logo
- Polished chrome finish

PRO-SET® SERVICE WRENCHES			
ltem	Description	Qty.	
TLSWL	${}^{3}/_{16}$ ", ${}^{1}/_{4}$ " Square Drive; ${}^{1}/_{2}$ ", ${}^{9}/_{16}$ " Hex Drive	1	
TLSWLB	$3/_{16}$ ", $1/_4$ " Square Drive; $1/_2$ ", $9/_{16}$ " Hex Drive (bulk pack)	100	
TLSWO	$3/_{16}$ ", $1/_{4}$ ", $5/_{16}$ ", $3/_{8}$ " Square Drive. Offset ends	1	
TLSWOB	$^{3}\!/_{16}",^{1}\!/_{4}",^{5}\!/_{16}",^{3}\!/_{8}"$ Square Drive. Offset ends (bulk pack)	100	
TLSWOA	$^{3}\!/_{16}",^{1}\!/_{4}",^{5}\!/_{16}",^{3}\!/_{8}"$ Square Drive. Offset ends. Includes $^{3}\!/_{16}"$ & $^{5}\!/_{16}"$ Hex Driver Bit	1	
TLSWS	³ / ₁₆ ", ¹ / ₄ ", ⁵ / ₁₆ ", ³ / ₈ " Square Drive	1	
TLSWSA	$^{3}\!/_{16}",^{1}\!/_{4}",^{5}\!/_{16}",^{3}\!/_{8}"$ Square Drive. Includes $^{3}\!/_{16}"$ & $^{5}\!/_{16}"$ Hex Driver Bit	1	
TLSWSB	³ / ₁₆ ", ¹ / ₄ ", ⁵ / ₁₆ ", ³ / ₈ " Square Drive (bulk pack)	100	



PRO-SET[®] TORQUE WRENCHES

Professional interchangeable jaw torque wrench set ensures compliance with OEM torque settings for high pressure systems.

- SAE (Inch) Or Metric Sets: Both include 6 sizes of interchangeable ends • •
 - Inch Wrench Settings in Inch-Pounds (60-960) or Foot-Pounds (5-80)
- Metric Wrench Settings in Newton-Meters (10-75) •
- Polished chrome finish •
 - Provides consistently accurate readings and rugged, trouble-free performance
 - Includes instruction sheet and molded storage case

PRO-SET [®] TORQUE WRENCHES				
I	MPERIAL	METRIC		
TLTWSAE	SAE Multi-Head Torque Wrench Set with handle, heads and case $({}^{5/_{8}}, {}^{11}/_{16}, {}^{13/_{16}}, {}^{15/_{16}}, {}^{11/_{16}}, {}^{15/_{16}})$	TLTWSM	Metric Multi-Head Torque Wrench Set with handle, heads and case (17, 22, 24, 26, 27, 29 mm)	
TLXTWSAE	Set of SAE Wrench Heads ${}^{5/8}_{8,"},{}^{11/16}_{16}{}^{,},{}^{13/16}_{16}{}^{,},{}^{15/16}_{16}{}^{,},{}^{11/16}_{16}{}^{,},{}^{15/16}_{16}{}^{,},{}^$	TLXTWM	Set of Metric Wrench Heads: 17, 22, 24, 26, 27, 29mm Jaw Sizes	
TLXTWSAEW	SAE Torque Wrench Handle	TLXTWMW	Metric Torque Wrench Handle	
INDIVIDUAL WRENCH HEADS				
TLXTW58	5/8"	TLXTWM17	17mm	
TLXTW1116	¹¹ / ₁₆ "	TLXTWM22	22mm	
TLXTW1316	¹³ / ₁₆ "	TLXTWM24	24mm	
TLXTW1516	¹⁵ / ₁₆ "	TLXTWM26	26mm	
TLXTW1L116	1 ¹ / ₁₆ "	TLXTWM27	27mm	
TLXTW1L516	1 ⁵ / ₁₆ "	TLXTWM29	29mm	



PRO-SET[®] SWAGE PUNCH SET 5 Punches (1/4", 5/16", 3/8", 1/2", 5/8") **PRO-SET[®] TUBE PIERCING PLIERS** Tube Piercing Pliers 1/4"





PRO-SET[®] PINCH-OFF & RE-ROUND TOOL Pinch-Off tool & rerounds 1/4", 5/16", 3/8", and 1/2" copper and tubing

TLPP



PINCH-OFF PLIERS

- Tool locks onto tubing to prevent loss of refrigerant during service
- Rounded jaws to avoid cutting tubing
- Fast release mechanism
- 1 year warranty



6-in-1 SWAGING PUNCH

- (3/16", 1/4", 5/16", 3/8", 1/2", 5/8")
- Swages six sizes of tubing
- Chrome plated for strength and durability



TLFC1 Universal Metal Fin Comb



TLFC6 Repair bent condenser fins with the TLFC6 Universal 6-sided fin comb straightening tool.



TLFC2 Fin Straightener with large durable, easy grip handle.

	9	
°	101	

TECH-SET [™] SERVICE WRENCHES Metal handles with frosted finish and blister card packaging			
Item	Description		
TSWS	Small Service Wrench: 3/16", 1/4", 5/16", 3/8" Square Drive		
TSWS0	Small Offset Service Wrench: 3/16", 1/4", 5/16", 3/8" Square Drive		
TSWSH	Large Service Wrench: $^{3}\!/_{16}$ & $^{1}\!/_{4}$ Square Drive; $^{1}\!/_{2}$ & $^{9}\!/_{16}$ Hex Drive		

TECH-SET™ INSPECTION MIRRORS

For fast, accurate inspection of any hidden area. Universal ball joints hold mirrors firmly at any angle.

