

RELÉS

PTC / RELÉS FRACCIONALES



Modelo	HP	Voltaje	Mínimo	Caja master
QRP-12E	1/2	115	25	25
QRP-13E	1/3	115	25	25
QRP-14E	1/4	115	25	25
QRP-15E	1/5	115	25	25
QRP-16E	1/6	115	25	25
QRP-18E	1/8	115	25	25
QPTC-999	1/10-1/3	110 V. / 12 A.	50	500

RELÉ/SOBRECARGA COMBO



Modelo	Descripción	Voltaje	Mínimo	Caja master
QRP-IC1	5 + - 20%	110	1	200
QRO-16	1/8, 1/6, 1/5	120	1	200



RELÉS DE ESTADO SÓLIDO

Modelo	Voltaje / Hz	Mínimo	Caja master
QSR-12E	115/60	25	250



RELÉS DE POTENCIALES

Modelo	Voltaje de la bobina	Pick Up Continuo	Pick Up Min	Pick Up Max	Drop Out Max	HP	Compresor Volt.	Mínimo	Caja master
QRP-63	170	139	153	55	1/4 a 1/2	115	25	100	
QRP-64	395	260	275	120	1 a 3	230	25	100	
QRP-65	332	168	182	90	1/2 a 1	115	25	100	
QRP-66	395	215	225	120	1 a 5	115 a 230	25	100	
QRP-67	420	295	315	125	1/2 a 5	208 a 230	25	100	



RELÉS PARA SERVICIO PESADO DEL VENTILADOR

Modelo	Contact Voltage VAC	Amp FLA	Amp LRA	Amp Res	Control de Estilo	Voltaje bobina VAC	Mínimo	Caja master
Q90-360	120/240/277	12/8/7	60/48/42	18	SPST-NO	24	1	100
Q90-370	120/240/277	12/8/7	60/48/42	18	SPDT	24	1	100
Q90-380	120/240/277	12/8/7	60/48/42	18	SPNO-SPNC	24	1	100

