

CONTACTORES

CONTACTORES

PROPÓSITOS DEFINIDO (2 POLOS)



Modelo	Voltaje de la bobina 50/60 Hz	Clasificación		Linea de voltaje	Peso	Mínimo	Caja master
		VA sellada	Amperio				
QCA-252	24	4.5	25	240-277	.6 lbs.	1	25
QCC-252	208-240	4.5	25	600	.6 lbs.	1	50
QCA-302	24	4.5	30	240-277	.6 lbs.	1	25
QCB-302	120	4.5	30	480	.6 lbs.	1	25
QCA-402	24	4.5	40	240-277	.6 lbs.	1	25
QCB-402	120	4.5	40	480	.6 lbs.	25	25
QCC-302	208-240	4.5	30	600	.6 lbs.	1	25
QCC-402	208-240	4.5	40	600	.6 lbs.	1	25

CONTACTORES

PROPÓSITOS DEFINIDO (3 POLOS)



Modelo	Voltaje de la bobina 50/60 Hz	Clasificación		Linea de voltaje	Peso	Mínimo	Caja master
		VA sellada	Amperio				
QCA-303	24	6	30	240-277	1 lb.	25	25
QCB-303	110-120	6	30	480	1 lb.	25	25
QCC-303	208-240	6	30	600	1 lb.	25	25
QCA-403	24	6	40	240-277	1 lb.	25	25
QCB-403	110-120	6	40	480	1 lb.	25	25
QCC-403	208-240	6	40	600	1 lb.	25	25
QCA-503	24	14	50	240-277	2 lbs.	1	24
QCB-503	110-120	14	50	480	2 lbs.	1	24
QCC-503	208-240	14	50	600	2 lbs.	1	24
QCA-603	24	14	60	240-277	2 lbs.	1	24
QCB-603	110-120	14	60	480	2 lbs.	1	24
QCC-603	208-240	14	60	600	2 lbs.	1	24
QCA-753	24	27	75	240-277	4 lbs.	1	12
QCB-753	110-120	27	75	480	4 lbs.	1	12
QCC-753	208-240	27	75	600	4 lbs.	1	12

